

DATASHEET

TUNER PRO FLEX



GENERAL

Art.Nr:	L-1019
GTIN:	8053841303054
E-class number:	40-21-08-13
Customs tariff number:	56090000

Standards:	PPE REGULATION
Net weight:	0.39 kg
Gross weight:	0.47 kg

DATASHEET

TUNER PRO FLEX

The multi-purpose rope has been specially developed for working on ropes, at height and for rescue purposes and impresses with its versatility thanks to a double regulator and a seamless holding rope that allows flexible connection directly to the harness. Despite its compact design and low weight, it is one of the most durable and resilient ropes on the market.

The patented regulator guarantees immediate and secure locking of the rope, regardless of the shape of the EN 362 compliant connector. Thanks to its special geometry, it allows precise and smooth control of the rope length, while releasing is intuitive and can be done with one hand: Simply hold the regulator and press the release button - even under a light load.

The lanyard complies with the EN 1891-A standard, is 9.6 mm thick, lightweight, flexible and designed for the most intensive use. It can be attached directly to the harness using a figure-of-eight knot and can also be configured as a "cow's tail" - ideal for rope work or for handling stretchers, even if this use is not part of the official certification. Elastic end loops allow the free rope ends to be positioned during use. The product complies with CE conformity and has been partially tested in accordance with EN 358.

MORE INFORMATION

TUNER PRO – Versatile lanyard for workplace positioning, restraint systems and rescue at height
<https://www.skylotec.com/eu_en/tunerpro>

FEATURES

Colour: Black, Orange

Maximum lifetime: 10 years

Min. temperature: -30 °C

Max. temperature: 50 °C

Patent status: Patent pending

Individually tested: No

100% quality control: Yes

DIMENSIONS

length_lanyard: 3.60 m

Lanyard rope diameter: 9.60 mm

MATERIAL

Material: Aluminium, Polyamide

DATASHEET
TUNER PRO FLEX

