

DATASHEET

SIRIUS



GENERAL

Art.Nr:	A-050	Standards:	ANSI/ASSP Z359.9-2021, EN 12841:
GTIN:	4030281286943		2006/C, EN 15151-1:2012, EN 341:
E-class number:	40-21-01-01	Net weight:	2011/2A, NFPA 2500:2022
Customs tariff number:	84798997		0.51 kg
		Gross weight:	0.51 kg

DATASHEET

SIRIUS

SIRIUS packs the advantages of the best descenders for industrial and rescue applications into an extremely compact design - for better handling and long service life. SIRIUS lies perfectly in your hand. The auto-returning operating lever has a particularly small radius of motion so that you can work fast, accurately, more comfortably and safely. During rope insertion, which is intuitive and simple, the carabiner on the harness can stay connected to the device. We designed the route of the rope in such a way that it is protected from twisting and kinking, and from excessive wear and tear. SIRIUS was developed for extended use under the toughest of conditions. That's why it is made of up to 100 % metal - without any vulnerable synthetic spots. SIRIUS. Best ergonomics and long service life in its most compact form.

FEATURES

Colour:	Black
Lifting function:	No
Max. abseiling height:	190 m
Maximum load 1 person:	141.00 kg
Maximum load 2 persons:	281.00 kg
Maximum lifetime:	30 years
Maximum number of persons:	2
Maximum load:	281.00 kg
Minimum compatible rope diameter:	9.00 mm
Maximum compatible rope diameter:	12.50 mm
Minimum tensile strength:	15.00 kN
Max. Abseil speed:	2.00 m/s
Minimum temperature:	-30 °C
Maximum temperature:	60 °C
Panic function:	Yes
Rescue function:	Yes

DIMENSIONS

Product length:	18.50 cm
Product width:	8.30 cm
Product height:	4.50 cm

MATERIAL

Material:	Aluminium, Steel
-----------	------------------

DATASHEET

SIRIUS

