


Univers	Professional
Type	Verticality
Category	Ropes
Subcategory	Low stretch kernmantel ropes




FLOW 11.8 mm

The FLOW 11.8 mm low stretch kernmantle rope is designed for tree care. Its medium diameter provides great performance in terms of flexibility and weight. The rope's low elongation under load increases efficiency when moving in the tree. EverFlex technology provides great flexibility and handling over time. It comes with a splice at one or two ends, for optimal rope glide through devices like a friction saver or pulley, and through tree branches. With a small splice, the rope can pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks. The rope is available in two colors and four lengths with one splice, and one length with two splices.



The rope's construction provides optimal performance when used with the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.



EverFlex technology provides great flexibility over time, allowing the rope to maintain excellent handling and optimal performance with devices.



The small size of the splice allows it to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.

Short Description Flexible and lightweight low stretch kernmantle rope for tree care

Selling Points

- Rope designed for tree care:
 - Patented splice at one or two ends for easier rope glide through devices like a friction saver or pulley, and through tree branches
 - Small splice allows the rope to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks
 - Low elongation under load increases efficiency when moving through the tree
- Medium diameter provides great performance in terms of flexibility and weight
- Consistent performance over time:
 - 100% polyester double weave construction
 - EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud), allowing it to maintain excellent handling and optimal performance with devices
- Available in two colors (green and orange), to help easily identify different work ropes
- Standard lengths: 25, 35, 45, and 60 meters with one splice, and 45 meters with two splices

Specification

- Diameter: 11,8mm
- Material(s): Polyester
- Certification(s): CE EN 1891 type A, ANSI Z133
- Weight per meter: 103g
- Strength: 27kN
- Strength tied with figure-eight knot: 15kN
- Strength with splice: 15kN
- Impact force (factor 0,3): 5,9kN
- Number of factor 1 falls: 6
- Construction: 24 carrier
- Percentage of sheath: 53%
- Static elongation: 3%

Specifications by reference

Reference(s)	R079DA06	R079DA07	R079DA00	R079DA01
Length	25 m	25 m	35 m	35 m
Color(s)	Green	Orange	Green	Orange
	1 splice	1 splice	1 splice	1 splice
Made in	FR	FR	FR	FR
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	4	4	4	4
EAN	3342540851122	3342540851139	3342540849112	3342540849129

Reference(s)	R079DA02	R079DA03	R079DA04	R079DA05
Length	45 m	45 m	60 m	60 m
Color(s)	Green	Orange	Green	Orange
	1 splice	1 splice	1 splice	1 splice
Made in	FR	FR	FR	FR
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	4	4	4	4
EAN	3342540849136	3342540849143	3342540849150	3342540849167

Reference(s)	R079EA00	R079EA01
Length	45 m	45 m
Color(s)	Green	Orange
	2 splices	2 splices
Made in	FR	FR
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	4	4
EAN	3342540849174	3342540849181

Related product(s)

- ZIGZAG®
- ZIGZAG® PLUS
- CHICANE
- TREESBEE®
- NAJA
- EJECT
- CONTROL 12.5 mm