

DATASHEET

OBX TG



GENERAL

Art.Nr:	H-400-TG	Standards:	EN 12275:2013, EN 12275:2013/B, EN 362:2004, EN 362:2004/B
GTIN:	8053841302705	Net weight:	0.08 kg
E-class number:	40-21-07-12	Gross weight:	0.11 kg
Customs tariff number:	76169990		

DATASHEET

OBX TG

Hot-forged light alloy oval connector with triplex gate. Designed for placing wide-section devices (e.g., pulleys, ascenders, fall arrest devices etc.).

Main features:

- oval shape for optimal positioning of devices and ropes;
- ergonomic shape which enables a good opening of the lever and improves handling;
- reinforced contact areas for better rope sliding and resistance to wear and tear;
- the line between the nose and the internal part of the connector is smooth and facilitates insertion and/or disconnection from anchors, tools and ropes;
- catch-free closure.

FEATURES

Colour:	Grey, Orange
---------	--------------

Gate opening:	22 mm
---------------	-------

MBS MAJOR AXIS:	24 kN
-----------------	-------

MBS MINOR AXIS:	12 kN
-----------------	-------

Form fit:	Key Lock
-----------	----------

Carabiner type:	Type B (EN 12275: 2013), Type B (EN 362:2004)
-----------------	---

Maximum lifetime:	30 years
-------------------	----------

Min. temperature:	-30 °C
-------------------	--------

Max. temperature:	50 °C
-------------------	-------

UIAA compliance:	Yes
------------------	-----

Individually tested:	Yes
----------------------	-----

Hot forged:	Yes
-------------	-----

Locking mechanism:	Trilock
--------------------	---------

DIMENSIONS

Product length:	112.00 mm
-----------------	-----------

Product width:	65.00 mm
----------------	----------

MATERIAL

Material:	Aluminium
-----------	-----------